

Product Information



3642ITP200P63 Flat

EAN 4031582337433

Swivel caster with total lock, leading end of caster, housing made of heavy pressed steel, bright zinc plated, blue passivated, precision ball bearing swivel head, sealed, wheel axle with nut. Wheel center made of Aluminum, Tread: Polyurethane, casted, precision ball bearing, plate fitting



Technical Data

| | |
|-------------------------|---------------------|
| Wheel diameter | 7.87 in |
| Tread width | 1.97 in |
| Plate size | 5.39 x 4.13 in |
| Plate hole centers | 4.13 x 3.15/2.95 in |
| Plate hole | 0.43 in |
| Offset | 2.17 in |
| Swivel Interference | 12.20 in |
| Overall height | 9.84 in |
| Temperature | - 4 / + 140 °F |
| Standard | EN 12532 |
| Weight | 8.913 lbs |
| Load capacity (dynamic) | 1325 lbs |
| Load capacity (static) | 2645 lbs |
| Hardness of tread | A 92 Shore |

| | | | | | |
|----------------------|---|---|---|---|---|
| Roll performance | + | + | + | + | + |
| Movement noise | + | + | + | + | + |
| Attrition | + | + | + | + | + |
| Corrosion resistance | + | + | + | + | + |

Product Information



3642ITP200P63 Flat

EAN 4031582337433

